

Express Mail No: EL627894581US

Attorney Docket: XY-Sonic-USNP

IN THE UNITED STATES PATENT AND  
TRADEMARK OFFICE

In Re the Application of: Kristopher S. Buchanan, Lisa Herickhoff, George Seidel, George C. Malachowski, Matthias J.G. Ottenberg, Douglas H. Ferguson

Serial Number: (original US) 60/075,612 (new) \_\_\_\_\_  
(PCT) PCT/US99/03638

Filed: (original US) 20 February 1998 (new) \_\_\_\_\_  
(PCT) 19 February 1999

For: A Vibratory System For A Sorting Flow Cytometer

Group Art Unit:

Examiner:

Assignee:

**LETTER OF TRANSMITTAL**

Assistant Commissioner for Patents  
BOX PCT  
Washington, D.C. 20231

Sir:

Enclosed for filing is an application for patent entitled "A Vibratory System For A Sorting Flow Cytometer" including the following documents:

1. a First Preliminary Amendment;
2. a Declaration for Patent Application of George C. Malachowski, Matthias J.G. Ottenberg and Douglas H. Ferguson;
3. a Declaration for Patent Application of Kristopher S. Buchanan and Lisa Herickhoff;
4. a Declaration for Patent Application of George Seidel;
5. a Power of Attorney of Cytomation, Inc., XY, Inc. and Colorado State University through its agent Colorado State University Research Foundation;

6. a Verified Statement Establishing Small Entity Status (Small Business) from Cytomation, Inc.;
7. a Verified Statement Establishing Small Entity Status (Small Business) from XY, Inc.;
8. a Verified Statement Establishing Small Entity Status 37 CFR 1.9(e) -- University or Other Institution of Higher Learning;
9. a Verified Statement Establishing Small Entity Status (University Employee);
10. a Assignment of Patent Rights of George C. Malachowski and Matthias J.G. Ottenberg along with a recordation cover sheet;
11. a Assignment of Patent Rights of Kristopher S. Buchanan, Lisa Herickhoff along with a recordation cover sheet;
12. a Assignment of Patent Rights of George Seidel along with a recordation cover sheet;
13. a true and correct copy of the Assignment of Patent Rights filed in the PCT application PCT/US99/03638 and recorded on February 2, 2000 from Douglas H. Ferguson to the Cytomation, Inc., recorded at reel/frame: 010570/0282, pursuant to 37 C.F.R. §3.21 and MPEP §306, and the corresponding Notice of Recordation and Recordation Cover Sheet;
14. a Transmittal Letter to the United States Designated/Elected Office (DO/EO/US) concerning a filing under 35 U.S.C. 371 (Form PTO-1390, rev 11-98) with attachments;
15. a copy of the International PCT application;
16. Information Disclosure Citation with some copies of the cited references;
17. Cashier's check payable to the Commissioner of Patents and Trademarks in the amount of \$ 2812.00;
18. this Letter of Transmittal; and
19. Express Mail Certificates for each document.

**Please address all future correspondence to: Santangelo Law Offices, P.C., 125 South Howes, Third Floor, Fort Collins, CO 80521.**

09/622621

533 Rec'd PCT/PTO 18 AUG 2000

I have this 8<sup>th</sup> day of August, 2000, either myself personally or through my direction of staff at this office, deposited all of the items in the above letter of transmittal with the United States Postal Service as Express Mail, postage prepaid, in an envelope addressed to: The Assistant Commissioner for Patents, Box Patent Application, Washington, D.C. 20231.

Dated this 8<sup>th</sup> day of August, 2000.

Respectfully Submitted,

SANTANGELO LAW OFFICES, P.C.

By:

  
Craig R. Miles

ATTORNEY FOR APPLICANT

PTO No. 45,954

125 South Howes, Third Floor

Fort Collins, Colorado 80521

(970) 224-3100

09/622621

533 Rec'd PCT/PTO 18 AUG 2000

Express Mail No: EL627894581US

Attorney Docket: XY-Sonic-USNP

IN THE UNITED STATES PATENT AND  
TRADEMARK OFFICE

In Re the Application of: Kristopher S. Buchanan, Lisa Herickhoff, George Seidel, George  
C. Malachowski, Matthias J.G. Ottenberg, Douglas H. Ferguson

Serial Number: (original US) 60/075,612 (new) \_\_\_\_\_  
(PCT) PCT/US99/03638

Filed: (original US) 20 February 1998 (new) \_\_\_\_\_  
(PCT) 19 February 1999

For: A Vibratory System For A Sorting Flow Cytometer

Group Art Unit:

Examiner:

Assignee:

**FIRST PRELIMINARY AMENDMENT**

Before examining the above-referenced application and before calculating application fees,  
please amend the application as follows:

**In the specification:**

Before the first sentence of the first paragraph of the application please insert --This  
application is the National Stage of International Application No. PCT/US99/03638, filed February  
19, 1999 which claims the benefit of United States Provisional Application No. 60/075,612, filed  
February 20, 1998, each hereby incorporated by reference.--

**In the claims:**

Please amend the claims as follows:

Claim 30 (once amended).

A portable oscillating device for a flow cytometer which oscillates an exterior surface of a flow cytometer nozzle as described in claim [28,] 29[, or 30] and further comprising a droplet shield coupled to said drop flow cytometer system between said exterior surface of said flow cytometer nozzle that forms droplets and an instrument surface of said flow cytometer system surface.

Claim 57 (once amended).

A flow cytometer system as described in claim 5[7]6 and further comprising a oscillation parameter selection element which operates said energy converter at selectable oscillation parameters.

Claim 95 (once amended).

A method of flow cytometry as described in claim [89, 90, or 93] 94 and further comprising the step of retaining said oscillation coupling element within said portable member cupping said exterior surface of said flow cytometer apparatus with a fluid retaining element having a first side affixed to said portable member and a second side which conforms to said exterior of said flow cytometer apparatus with said first side and said second side and said surface configured to cup said exterior surface of said flow cytometer apparatus.

96. A method of flow cytometry as described in claim [89, 90, 93, or 94] 89 and further comprising the step of selecting said mechanical oscillations created by said energy converter by selecting said parameter from an oscillation selection element.
99. A method of flow cytometry as described in claim [89, 90, 93, or 94] 96 and further comprising the step of sweeping a range of oscillations.
100. A method of flow cytometry as described in claim [89, 90, 93, or 94] 89 and further comprising the step of moving said portable member with an automated moving system.

## REMARKS

This application is the National Stage of International Application No. PCT/US99/03638, filed February 19, 1999 which claims the benefit of United States Provisional Application No. 60/075,612, filed February 20, 1998. The International Application presented claims 1-109 for examination. All the claims were examined and met the criteria set out in PCT Article 33(2)-(4) with respect to novelty, inventive step, and industrial applicability.

The office raised concerns with regard to clarity under Rule 66.2(a)(v) PCT with regard to claims 30, 57-61, and 95-104 because claims 30 and 57 were dependent upon themselves, and because claims 30, 95, 96, 99, and 100 presented multiple dependent claims which were dependent upon multiply dependent claims. Claims 30, 57, 95, 96, 99, and 100 have been amended as set forth above to avoid claim dependency upon themselves or multiple dependent claims upon multiple dependent claims so as to address each of the office's concerns.

The applicant having amended the claims as set out above now believes that each of claims 1-109 is in condition for allowance.

## CONCLUSION


The applicant submits this Preliminary Amendment to address the office's concerns regarding the clarity of claims 30, 57-61, and 95-104. These claims have been amended to address claims which are dependent upon themselves or are multiple claims which are dependent upon multiple claims. The applicant respectfully requests allowance of claims 1-109 at the examiner's earliest convenience.

Dated this 18<sup>th</sup> day of August, 2000.

Respectfully Submitted,

SANTANGELO LAW OFFICES, P.C.

By:

  
Craig R. Miles

ATTORNEY FOR APPLICANT

PTO No. 45,954

125 South Howes, Third Floor

Fort Collins, Colorado 80521

(970) 224-3100

09/622621  
533 Rec'd PCT/PTO 18 AUG 2000

Express Mail No: EL627894581US

Attorney Docket: XY-Sonic-USNP

IN THE UNITED STATES PATENT AND  
TRADEMARK OFFICE

In Re the Application of: Kristopher S. Buchanan, Lisa Herickhoff, George Seidel, George C. Malachowski, Matthias J.G. Ottenberg, Douglas H. Ferguson

Serial Number: (original US) 60/075,612 (new) \_\_\_\_\_  
(PCT) PCT/US99/03638

Filed: (original US) 20 February 1998 (new) \_\_\_\_\_  
(PCT) 19 February 1999

For: A Vibratory System For A Sorting Flow Cytometer

Group Art Unit:

Examiner:

Assignee:

**CERTIFICATE OF EXPRESS MAILING**

I, Shannon Nation-Kammerer, hereby certify to the truth of the following items:

1. I am an employee of Santangelo Law Offices, P.C., 125 South Howes, Third Floor, Fort Collins, Colorado 80521.

2. I have this day deposited the attached Preliminary Amendment with the United States Postal Service as "Express Mail" for mailing to the Assistant Commissioner of Patents, Box PCT, Washington, D.C. 20231.

Dated this 18 day of August, 2000.

Shannon N. Nation-Kammerer



Express Mail No: EL627894581US

Attorney Docket: XY-Sonic-USNP

**IN THE UNITED STATES PATENT AND  
TRADEMARK OFFICE**

In Re the Application of: Kristopher S. Buchanan, Lisa Herickhoff, George Seidel, George C. Malachowski, Matthias J.G. Ottenberg, Douglas H. Ferguson

Serial Number: (original US) 60/075,612 (new) \_\_\_\_\_  
(PCT) PCT/US99/03638

Filed: (original US) 20 February 1998 (new) \_\_\_\_\_  
(PCT) 19 February 1999

For: A Vibratory System For A Sorting Flow Cytometer

Group Art Unit:

Examiner:

Assignee:

**VERIFIED STATEMENT ESTABLISHING SMALL ENTITY STATUS  
(SMALL BUSINESS CONCERN)**


I, Nigel M. Ferrey as President of Cytomation, Inc., pursuant to 37 C.F.R. Section 1.27(c) state that the following facts are true:

1. I am President of Cytomation, Inc. As such I am empowered to act on behalf of the Assignee.

2. As set forth in 37 C.F.R. Section 121.12, Cytomation, Inc. is an entity whose number of employees, including those of its affiliates, does not exceed 500 persons and which has not assigned, granted, conveyed, or licensed, and is under no obligation under contract or law to assign, grant, convey or license, any rights in the subject matter of the enclosed Patent Application. Exclusive rights to the invention have been conveyed to and remain with Cytomation, Inc. Cytomation, Inc. appears to qualify as a small business concern as defined in 37 C.F.R. Section 1.9(d).

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.


MADE this 8 day of August, 2000.

By:   
Nigel M. Ferrey as President of Cytomation, Inc.


UNITED STATES OF AMERICA )  
STATE OF COLORADO ) ss.  
COUNTY OF LARIMER )

SUBSCRIBED AND AFFIRMED OR SWORN to before me in the County of Larimer, State of Colorado, United States of America, by Nigel M. Ferrey, this 8 day of August, 2000.

WITNESS my hand and official seal pursuant to the authority vested in me as a Notary Public by the State of Colorado.



My Commission Expires 07/15/2003

  
Notary Public  
My Commission Expires: 7-15-2003

533 Rec'd PCT/PTO 18 AUG 2000

Express Mail No: EL627894581US

Attorney Docket: XY-Sonic-USNP

---

IN THE UNITED STATES PATENT AND  
TRADEMARK OFFICE

---

In Re the Application of: Kristopher S. Buchanan, Lisa Herickhoff, George Seidel, George  
C. Malachowski, Matthias J.G. Ottenberg, Douglas H. Ferguson

Serial Number: (original US) 60/075,612 (new) \_\_\_\_\_  
(PCT) PCT/US99/03638

Filed: (original US) 20 February 1998 (new) \_\_\_\_\_  
(PCT) 19 February 1999

For: A Vibratory System For A Sorting Flow Cytometer

Group Art Unit:

Examiner:

Assignee:

---

**CERTIFICATE OF EXPRESS MAILING**

I, Shannon Nation-Kammerer, hereby certify to the truth of the following items:

1. I am an employee of Santangelo Law Offices, P.C., 125 South Howes, Third Floor, Fort Collins, Colorado 80521.
2. I have this day deposited the attached Verified Statement Establishing Small Entity Status (Small Business) from Cytomation, Inc. with the United States Postal Service as "Express Mail" for mailing to the Assistant Commissioner of Patents, Box PCT, Washington, D.C. 20231.

Dated this 18 day of August, 2000.

Shannon N. Nation-Kammerer

Express Mail No: EL627894581US

Attorney Docket: XY-Sonic-USNP

---

IN THE UNITED STATES PATENT AND  
TRADEMARK OFFICE

---

In Re the Application of: Kristopher S. Buchanan, Lisa Herickhoff, George Seidel, George  
C. Malachowski, Matthias J.G. Ottenberg, Douglas H. Ferguson

Serial Number: (original US) 60/075,612 (new) \_\_\_\_\_  
(PCT) PCT/US99/03638

Filed: (original US) 20 February 1998 (new) \_\_\_\_\_  
(PCT) 19 February 1999

For: A Vibratory System For A Sorting Flow Cytometer

Group Art Unit:

Examiner:

Assignee:

---

**VERIFIED STATEMENT ESTABLISHING SMALL ENTITY STATUS  
(SMALL BUSINESS CONCERN)**

I, Dr. Mervyn Jacobson as President of XY, Inc., pursuant to 37 C.F.R. Section 1.27(c) state that the following facts are true:

1. I am President of XY, Inc. As such I am empowered to act on behalf of the Assignee.
2. As set forth in 37 C.F.R. Section 1.21, XY, Inc. is an entity whose number of employees, including those of its affiliates, does not exceed 500 persons and which has not assigned, granted, conveyed, or licensed, and is under no obligation under contract or law to assign, grant, convey or license, any rights in the subject matter of the enclosed Patent Application. Exclusive rights to the invention have been conveyed to and remain with XY, Inc. XY, Inc. appears to qualify as a small business concern as defined in 37 C.F.R. Section 1.9(d).

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

MADE this 8 day of August, 2000.

By:

Dr. Mervyn Jacobson as President of XY, Inc.

UNITED STATES OF AMERICA )  
STATE OF COLORADO )ss.  
COUNTY OF LARIMER )

SUBSCRIBED AND AFFIRMED OR SWORN to before me in the County of Larimer, State of Colorado, United States of America, by Dr. Mervyn Jacobson, this 8 day of August, 2000.

WITNESS my hand and official seal pursuant to the authority vested in me as a Notary Public by the State of Colorado.

Shannon M. Nation-Kammerer  
Notary Public  
My Commission Expires: 7-15-2003



My Commission Expires 07/15/2003

09/622621

533 Rec'd PCT/PTO 18 AUG 2000

Express Mail No: EL627894581US

Attorney Docket: XY-Sonic-USNP

**IN THE UNITED STATES PATENT AND  
TRADEMARK OFFICE**

In Re the Application of: Kristopher S. Buchanan, Lisa Herickhoff, George Seidel, George C. Malachowski, Matthias J.G. Ottenberg, Douglas H. Ferguson

Serial Number: (original US) 60/075,612 (new) \_\_\_\_\_  
(PCT) PCT/US99/03638

Filed: (original US) 20 February 1998 (new) \_\_\_\_\_  
(PCT) 19 February 1999

For: A Vibratory System For A Sorting Flow Cytometer

Group Art Unit:

Examiner:

Assignee:

**CERTIFICATE OF EXPRESS MAILING**

I, Shannon Nation-Kammerer, hereby certify to the truth of the following items:

1. I am an employee of Santangelo Law Offices, P.C., 125 South Howes, Third Floor, Fort Collins, Colorado 80521.

2. I have this day deposited the attached Verified Statement Establishing Small Entity Status (Small Business) from XY, Inc. with the United States Postal Service as "Express Mail" for mailing to the Assistant Commissioner of Patents, Box PCT, Washington, D.C. 20231.

Dated this 18 day of August, 2000.

Shannon M. Nation-Kammerer

Express Mail No: EL627894581US

Attorney Docket:XY-Sonic-USNP

---

IN THE UNITED STATES PATENT AND  
TRADEMARK OFFICE

---

In Re the Application of: Kristopher S. Buchanan, Lisa Herickhoff, George Seidel, George  
C. Malachowski, Matthias J.G. Ottenberg, Douglas H. Ferguson

Serial Number: (original US) 60/075,612 (new) \_\_\_\_\_  
(PCT) PCT/US99/03638

Filed: (original US) 20 February 1998 (new) \_\_\_\_\_  
(PCT) 19 February 1999

For: A Vibratory System For A Sorting Flow Cytometer

Group Art Unit:

Examiner:

Assignee:

---

**VERIFIED STATEMENT ESTABLISHING SMALL ENTITY STATUS  
(UNIVERSITY EMPLOYEE)**

I, George E. Seidel, as an above named inventor of the invention described in the specification filed herewith with title as listed above, hereby declare that all actions involving the creation of the above referenced invention were taken by me as an employee who has acted on behalf of Colorado State University a non-profit organization as defined in 37 C.F.R. 1.9(e) for purposes of paying reduced fees to the Patent and Trademark Office.

I have not assigned, granted, conveyed or licensed and am under no obligation under contract or law to assign, grant, convey or license, any rights in the invention to any person who would not qualify as a small business concern under 37 C.F.R. 1.9(d) or a nonprofit organization under 37 C.F.R. 1.9(e).

Each person, concern, or organization to which I have assigned, granted, conveyed, or licensed or am under an obligation under contract or law to assign, grant, convey, or license any rights in the invention is listed below:

Colorado State University  
c/o Colorado State University Research Foundation  
601 South Howes Street, Room 410  
Fort Collins, CO 80523

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

MADE UNDER OATH this 16<sup>th</sup> day of August, 2000.

George E. Seidel  
George E. Seidel

UNITED STATES OF AMERICA )  
STATE OF COLORADO )ss.  
COUNTY OF LARIMER )

SUBSCRIBED AND SWORN to before me in the County of Larimer, State of Colorado, United States of America, by George E. Seidel as Inventor, this 16<sup>th</sup> day of August, 2000.

WITNESS my hand and official seal pursuant to the authority vested in me as a Notary Public by the State of Colorado.

Dein Marie Kommer  
Notary Public  
My Commission Expires: 4-9-2004



09/622621

533 Rec'd PCT/PTO 18 AUG 2000

Express Mail No: EL627894581US

Attorney Docket: XY-Sonic-USNP

IN THE UNITED STATES PATENT AND  
TRADEMARK OFFICE

In Re the Application of: Kristopher S. Buchanan, Lisa Herickhoff, George Seidel, George  
C. Malachowski, Matthias J.G. Ottenberg, Douglas H. Ferguson

Serial Number: (original US) 60/075,612 (new) \_\_\_\_\_  
(PCT) PCT/US99/03638

Filed: (original US) 20 February 1998 (new) \_\_\_\_\_  
(PCT) 19 February 1999

For: A Vibratory System For A Sorting Flow Cytometer

Group Art Unit:

Examiner:

Assignee:

**CERTIFICATE OF EXPRESS MAILING**

I, Shannon Nation-Kammerer, hereby certify to the truth of the following items:

1. I am an employee of Santangelo Law Offices, P.C., 125 South Howes, Third Floor, Fort Collins, Colorado 80521.

2. I have this day deposited the attached Verified Statement Establishing Small Entity Status (University Employee) with the United States Postal Service as "Express Mail" for mailing to the Assistant Commissioner of Patents, Box PCT, Washington, D.C. 20231.

Dated this 18 day of August, 2000.

Shannon M. Nation-Kammerer

Express Mail No: EL627894581US

Attorney Docket: XY-Sonic-USNP

**IN THE UNITED STATES PATENT AND  
TRADEMARK OFFICE**

In Re the Application of: Kristopher S. Buchanan, Lisa Herickhoff, George Seidel, George C. Malachowski, Matthias J.G. Ottenberg, Douglas H. Ferguson

Serial Number: (original US) 60/075,612 (new) \_\_\_\_\_  
(PCT) PCT/US99/03638

Filed: (original US) 20 February 1998 (new) \_\_\_\_\_  
(PCT) 19 February 1999

For: A Vibratory System For A Sorting Flow Cytometer

Group Art Unit:

Examiner:

Assignee:

**VERIFIED STATEMENT ESTABLISHING SMALL ENTITY STATUS  
37 CFR 1.9(e)--UNIVERSITY OR OTHER INSTITUTION OF HIGHER LEARNING**

I hereby declare that I am an official empowered to act on behalf of the University identified below:

Colorado State University  
c/o Colorado State University Research Foundation  
601 South Howes Street, Room 410  
Fort Collins, CO 80523

Type of nonprofit organization: University.

I hereby declare that the nonprofit organization identified above is a University or other Institution of Higher Education and therefore qualifies as a nonprofit organization as defined in 37 CFR 1.9(e) for purposes of paying reduced fees to the United States Patent and Trademark Office regarding the invention described in the specification filed herewith with title as listed above.

I hereby declare, to the best of my knowledge, rights under contract or law have been conveyed to and remain with the nonprofit organization except for an exclusive license which has been granted to XY, Inc.

I hereby declare that no rights to the invention are held by any concern which would not qualify as a small business concern under 37 CFR 1.9(d).


Each person, concern, or organization having any rights in the invention is listed below:

- 1) Colorado State University  
c/o Colorado State University Research Foundation  
P. O. Box 483  
Fort Collins, CO 80523
- 2) XY, Inc.  
3801 Rampart Road  
ARBL Building  
Fort Collins, CO 80523
- 3) Cytomation, Inc.  
4850 Innovation Drive  
Fort Collins, CO 80525

I acknowledge the duty to file, in this application, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

Made under OATH this 16<sup>th</sup> day of August, 2000.

By:   
Arundeeep S. Pradhan, Director of Technology Transfer  
for Colorado State University Research Foundation  
agent for Colorado State University

UNITED STATES OF AMERICA )  
STATE OF COLORADO ) ss.  
COUNTY OF LARIMER )

SUBSCRIBED AND SWORN to before me in the County of Larimer, State of Colorado, United States of America, by Arundeeep S. Pradhan, this 16<sup>th</sup> day of August, 2000.

WITNESS my hand and official seal pursuant to the authority vested in me as a Notary Public by the State of Colorado.

*Dawn Marie Kommejer*  
Notary Public  
My Commission Expires: 4-9-2004

09/622621

533 Rec'd PCT/PTO 18 AUG 2000

Express Mail No: EL627894581US

Attorney Docket: XY-Sonic-USNP

IN THE UNITED STATES PATENT AND  
TRADEMARK OFFICE

In Re the Application of: Kristopher S. Buchanan, Lisa Herickhoff, George Seidel, George  
C. Malachowski, Matthias J.G. Ottenberg, Douglas H. Ferguson

Serial Number: (original US) 60/075,612 (new) \_\_\_\_\_  
(PCT) PCT/US99/03638

Filed: (original US) 20 February 1998 (new) \_\_\_\_\_  
(PCT) 19 February 1999

For: A Vibratory System For A Sorting Flow Cytometer

Group Art Unit:

Examiner:

Assignee:

**CERTIFICATE OF EXPRESS MAILING**

I, Shannon Nation-Kammerer, hereby certify to the truth of the following items:

1. I am an employee of Santangelo Law Offices, P.C., 125 South Howes, Third  
Floor, Fort Collins, Colorado 80521.

2. I have this day deposited the attached Verified Statement Establishing Small  
Entity Status 37 CFR 1.9(e) -- University or Other Institution of Higher Learning with the United  
States Postal Service as "Express Mail" for mailing to the Assistant Commissioner of Patents,  
Box PCT, Washington, D.C. 20231.

Dated this 18 day of August, 2000.

Shannon N. Nation-Kammerer

09/622621

533 Rec'd PCT/PTO 18 AUG 2000

Express Mail No: EL627894581US

Attorney Docket: XY-Sonic-USNP

IN THE UNITED STATES PATENT AND  
TRADEMARK OFFICE

In Re the Application of: Kristopher S. Buchanan, Lisa Herickhoff, George Seidel, George  
C. Malachowski, Matthias J.G. Ottenberg, Douglas H. Ferguson

Serial Number: (original US) 60/075,612 (new) \_\_\_\_\_  
(PCT) PCT/US99/03638

Filed: (original US) 20 February 1998 (new) \_\_\_\_\_  
(PCT) 19 February 1999

For: A Vibratory System For A Sorting Flow Cytometer

Group Art Unit:

Examiner:

Assignee:

**CERTIFICATE OF EXPRESS MAILING**

I, Shannon Nation-Kammerer, hereby certify to the truth of the following items:

1. I am an employee of Santangelo Law Offices, P.C., 125 South Howes, Third Floor, Fort Collins, Colorado 80521.
2. I have this day deposited the attached firm Letter of Transmittal and a cashier's check in the amount of \$ 2,812.00 with the United States Postal Service as "Express Mail" for mailing to the Assistant Commissioner of Patents, Box PCT, Washington, D.C. 20231.

Dated this 18 day of August, 2000.

Shannon Nation-Kammerer

A VIBRATORY SYSTEM FOR A SORTING FLOW CYTOMETER

533 Rec'd PCT/PTO 18 AUG 2000

**I. TECHNICAL FIELD**

This invention relates to a flow cytometry system and methods of operating both analytical and drop flow cytometers including apparatus and methods of unclogging or  
5 dislodging of media or gas from the inside of devices which may become clogged. Specifically, the invention focuses upon a device which may be used to unclog nozzles, dislocate gas, or clean exterior surfaces of flow cytometers used in the cytometry industry, which are subject to clogging, entrapping gas, or collecting adherents to exterior surfaces.

**II. BACKGROUND**

10 The desire to unclog, dislocate entrapped gas, and clean nozzles or a nozzle body has been known in some industries for many years. This desire has been quite acute for quite some time in the cytometry field. Cytometers are sometimes used to separate or sort particles from one another based upon the differences detected by shining a high intensity light upon  
15 each particle then discerning differences between the amount of light reflected from each particle. These particles may be quite variable based upon the application of the user. They may be biological cells of plant or animal matter or particles of other materials. All of these various particles will vary in size, shape, homogeneity, texture, and adhesion properties.

As shown in Fig. 1, the sheath fluid (8) is forced into the nozzle chamber (11) surrounding the sample tube or sample introduction element (9) at the same time that the  
20 sample is injected through the sample tube into the nozzle chamber. Both fluids travel down the chamber with the sample remaining in the center of the chamber. In an ideal sorting-type of setup the sample particles travel in line to the orifice where they exit a microscopic nozzle orifice or nozzle aperture (13) (typically 50-250 microns) into the free fall area within which droplets form and fall. Generally, at this point, the characteristics of the sample are  
25 determined at high speeds, sometimes as rapidly as 40,000 drops per second. In the typical application, the samples are then sorted at high speeds into containers based upon the detected characteristics. Thus, predictability and consistency are crucial to accurate detection

and to accurate sorting of the samples. Unwelcome variations in the stream emanating from the nozzle, either in volume or in direction or both, may have significant effects on the ability of the user to provide accurate results.

5 In practice, particles and gas in the sheath fluid or nozzle aperture adherents or the sample particles injected into the nozzle chamber accumulate faster than they can exit the nozzle and can begin filling the nozzle chamber or occluding the nozzle aperture with sample particles or gas bubbles. This accumulation of particles or gas can cause partial or total clogs in the nozzle or nozzle aperture. Figs. 1, 2 and 3 show a typical cytometer nozzle or exterior surface of a flow cytometer nozzle and area in which such clogging may occur. The problem  
10 of clogged nozzles also causes problems relating to the limited shelf life of samples which may be biological in nature and any delays relating to equipment malfunction may require completely starting an experiment from scratch.

Another source of nozzle clogs is related to homogeneity of the sample. The sample preparer, for some reason, may be unable to filter the sample prior to sorting it on the  
15 cytometer or the filtered samples may agglutinate. In this case, some of the particles may be larger than the nozzle orifice which will immediately cause clogs.

More specifically, significant advances on sorting sperm for a variety of purposes have been made in recent years. Yet, this type of sample is especially prone to clogging. At present, the only quantitative technique used to achieve the separation of X- and Y-  
20 chromosome bearing sperm has been that involving individual discrimination and separation of the sperm through the techniques of flow cytometry. This technique appeared possible as a result of advances and discoveries involving the quantitative dye absorption of X- and Y- chromosome bearing sperm. This was discussed early in U.S. Patent No. 4362246 and significantly expanded upon through the techniques disclosed by Lawrence Johnson in U.S.  
25 Patent No. 5135759. The Johnson technique of utilizing flow cytometry to separate X- and Y- chromosome bearing sperm has been so significant an advancement that it has for the first time made the commercial separation of such sperm feasible. While still experimental, separation has been significantly enhanced through the utilization of high speed flow cytometers such as the MoFlo® flow cytometer produced by Cytomation, Inc. and discussed



in a variety of other patents including U.S. Patent Nos. 5150313, 5602039, 5602349, and 5643796 as well as international PCT patent publication WO 96/12171. While the utilization of Cytomation's MoFlo® cytometers has permitted great increases in speed, and while these speed increases are particularly relevant given the high number of sperm often used, certain problems have still remained. In spite of the almost ten-fold advances in speed possible by the MoFlo® flow cytometer, shorter and shorter sorting times have been desired for several reasons. First, it has been discovered that as a practical matter, the sperm are time-critical cells. Their fertility decreases with increased delay time. Second, the collection, sorting, and insemination timings has made speed an item of high commercial importance. Thus, the time critical nature of the sperm cells and the process has made speed an essential element in achieving high efficacy and success rates. Naturally, clogging which greatly increases the time required for sorting of the sperm, can be debilitating to the entire success of the process.

Clogging can also occur from the particular sheath fluid used in cytometry operations. The sheath fluid typically used on a cytometer is that of a saline solution including other additives as needed. This saline may form salt crystals on the outside on the nozzle orifice and slowly restrict the exit orifice of the nozzle or otherwise disturb the natural spraying direction of the nozzle. This may result in a partial or complete clog of the nozzle, and can exacerbate problems caused by sample clumping.

Perhaps one of the most significant problems that those in some fields have faced is that of clearing the orifice of the nozzle without damaging it in some way. While this basic concept seems quite simple, implementation is not so straightforward. The operator or other user was faced with the decision to attempt unclogging in situ while it is attached to the cytometer and properly aligned or to remove the nozzle, clean it and then restart the very tedious and slow realignment steps which are necessary if the nozzle is removed before it can be used again for sorting.

One concept put forward for clearing a nozzle in situ involves inserting a thin wire or similar device into the orifice of the nozzle. While this may seem quite straightforward, the problem of finding the orifice of the nozzle which may be 50 to 250 microns in diameter is quite difficult. Further the small diameter of the wire would make it far too delicate to

practically thread into the orifice. Another complication to this approach is the small and difficult-to-reach area where a cytometer nozzle is typically located on the instrument. Even if the aforementioned problems were overcome, the nozzle would likely become damaged as a result of the insertion.

5 Another concept which has been discussed involves the use of applying a vacuum from the outside of the nozzle orifice, which suffers from a clog or particle. This approach has practical limitations involving sealing around the exterior of the nozzle to allow a vacuum to develop. A vacuum source would need to be generated of sufficient magnitude to be of benefit to the nozzle. This approach is complicated by touching the nozzle in situ and thereby  
10 disturbing its sensitive alignment and flow path. Potentially, the vacuum source could make a nozzle clog worse by pulling the particulates inside the nozzle closer and packing them harder into the orifice. Even if a nozzle is unclogged by this method, the operator might be forced to realign the cytometer before using the cytometer.

15 Another concept used solely in the context of analytical cytometers which do not form droplets is the use of a piezoelectric crystal to set up localized vibrations around the sample injector or sensing aperture for declogging. This concept, shown in US Patent No. 4,673,288 however, has never been developed or applied for a system compatible with the unique requirements of drop flow cytometry for dislocation of particles. Moreover, the disclosure of using oscillations with respect to analytical flow cytometry teaches the use of  
20 pressure change to dislocate gas which teaches away from the disclosed invention.

25 Another problem particular to cytometry and addressed by this invention is that of trapped air bubbles or gas in the fluidic components of a cytometer. The bubbles can form a compressible medium in the nozzle chamber that affects the precision alignment of the flow stream. In practice, the bubbles are sometimes difficult to remove from the chamber or debubble the chamber due, perhaps, to surface tension of the bubble to the walls of the chamber and within the sheath fluid itself. An operator generally is delayed in processing the sample through the cytometer when bubbles are present in the nozzle chamber, thus reducing the efficiency of the process. The cytometer operator previously had no tool to address the problem of trapped gases and had no choice but to wait some amount of time, which would

vary greatly, and allow the bubbles to naturally migrate to areas of lesser concern.

Another concern particular to drop flow cytometry systems is in situ cleaning of either the exterior or the interior of the drop flow cytometer nozzle. Adherents which collect on the nozzle disturb the flow path and alignment with the flow path sensing system. Routine  
5 cleaning of the nozzle surfaces can maintain the flow path and alignment parameters without having to disassemble the nozzle and clean the parts separate from the drop flow cytometer. Previously, no tool existed to address the problem of cleaning such surfaces of the drop flow cytometer nozzle.

As to both the cytometry industry and the overall desire to unclog nozzles in situ in  
10 any industry, the present invention discloses techniques which overcome virtually every one of the previous problems in a practical fashion. Perhaps surprisingly, it satisfies a long-felt need to achieve unclogging, de-bubbling and cleaning of a nozzle in situ with little or no damage to the nozzle and without significantly disturbing it in any way. It is perhaps surprising to those involved in the use of cytometers to see how the problem could be solved  
15 in a safe, economical manner without requiring the removal of nozzles.

### III. DISCLOSURE OF INVENTION

The present invention includes a variety of aspects which may be selected in different combinations to suit the needs of the user. First, it can function as a nozzle unclogging tool or cleaning tool for a cytometer nozzle or any nozzle which has been partially clogged. Second,  
20 it can be used as an unclogging tool for a cytometer nozzle or any nozzle which has become fully clogged or has a particle entrapped. In a basic form, the concept involves taking a source of vibratory energy or using an energy converter which creates mechanical oscillations (as selected with a oscillation selection element or by sweeping a range of oscillations), and with a media or oscillation coupling element present (such as a fluid, gel or other appropriate media) or through  
25 a mechanical couple, and transferring the energy from the source and presenting (coupling) it to the problem area or to allow the media in cooperation with the vibration (either ultrasonic or subsonic) to dislodge any matter in the nozzle which may be causing the clog. Such a technique offers advantages to the operator of the cytometer in allowing machine downtime and any

resulting realignment to be greatly reduced, thereby making the operation of a cytometer to be more predictable and increasing the likelihood of successfully sorting a particular sample. Third, it can function as a de-bubbling tool to aid the cytometer operator in removing bubbles from a cytometer. This device excites the nozzle and surrounding fluid in such a way that the air quickly migrates to areas where it can be removed. The invention does this by providing a means for a vibratory chamber of media in which to immerse the nozzle, especially the orifice of the nozzle, into the vibrating media in the chamber while the nozzle is still mounted and fluidically attached or by means of mechanical coupling to the exterior surface of the nozzle.

Based upon testing which has occurred to date, it functions particularly well on partially clogged nozzles. It appears to typically unclog these nozzles and allow the cytometer stream to return to its original position, thereby eliminating the need for adjustment, so typical prior to the present invention.

One of the broad objects of the invention is to allow for an unclogging tool or portable member configured so as to mechanically couple mechanical oscillations to the exterior of the nozzle to be used while the nozzle is present on the cytometer, in situ. Thus, one goal includes making the device small enough to fit within the existing spaces surrounding the nozzle on cytometers. Another goal would be to allow a means for the device to be moved into position or have a portable member such that the chamber or portable surface configured so as to mechanically couple mechanical oscillations to the exterior of the nozzle is presenting the vibratory media to the nozzle orifice or nozzle exterior and then easily removed from this area such that normal cytometer functions can take place. This goal may be accomplished manually (hand held) such as with a portable device or may be automated with a more permanently mounted unit or automated movement that retracts and engages the nozzle. Likewise, it may be manually activated independent of flow cytometer operation conditions when the operator notices a variation in the processing or it may be automated by sensors detecting a clogging or in response to flow cytometer conditions.

Another goal would be to allow the use of such a device that will not harm the nozzle. A goal for this invention is to unclog the nozzle while preventing any aspects to the procedure which could effect the positioning of the nozzle or the original condition of the nozzle orifice.

Another broad object of the invention is to provide a means of removing air bubbles from the nozzle or debubbling. Some of the goals for this object remain the same as for unclogging in that the device is generally small enough to fit in the space allowed and may be easily moved out of the way after use. A further goal would be to allow the cytometer operator to pull a vacuum on the inside of the nozzle chamber while presenting a surface configured so as to mechanically couple mechanical oscillations to the exterior of the nozzle or a chamber of media to the nozzle and vibrating the media and therefore the nozzle with sufficient energy that any air bubbles in the nozzle will no longer cling to the sides of the nozzle, but will rise to areas where they may be removed through fluidic hoses and tubes.

Yet another goal would be to allow for different cytometer nozzles on different cytometer machines to be unclogged and debubbled with this invention. Further, it is a goal to provide this in an economical manner such that it is affordable to the cytometry user.

#### IV. BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a side view of a nozzle assembly showing the sample tube, inner cavity, sheath fluid, orifice and the positioning of an oscillating portable member, oscillation coupling element, and fluid retaining element.

Fig. 2 is a photo of a typical drop flow cytometer nozzle assembly, showing on one end the nozzle through which is an orifice which may become clogged.

Fig. 3 is a photo of a typical cytometer and a nozzle in situ where it would become clogged.

Fig. 4 is a photo of the preferred embodiment being portable and having a vibration generator or energy source (1), flexible cable transfer element (2), and energy converter (3) which may be used to provide energy to the probe or portable member (4).

Fig. 5 is a photo of a probe or portable member (4) which is one embodiment of the invention which has a cavity or cup surface (7), an attachment end or joining element (5), and activating end (6).

5 Fig. 6 is a sketch of a side view of a probe (4) showing the cavity cup surface (7), an attachment end (5), and activating end (6).

Fig. 7 is a sketch of a probe (4) and cavity or cup surface (7) as part of an alternative embodiment being more of a permanent installation which may be mounted to a cytometer and which allows these components to move to the nozzle area and then be moved aside.

10 Fig. 8 is a sketch of a probe (4) with a media trap or instrument shield (12) and a liquid evacuation element ( ) which could be employed in an alternative embodiment to collect any liquids or media before they could collect in an unwanted area.

## V. BEST MODE FOR CARRYING OUT THE INVENTION

15 The preferred embodiment is that of a probe or portable member which includes a surface configured to mechanically couple oscillation to the exterior of the flow cytometer nozzle or a cavity which holds a media (such as a fluid, gel, or other appropriate energy transferring media) which creates a bath or oscillations coupling element which may be vibrating. This cavity is presented to the nozzle, especially the orifice area, and allows the nozzle orifice to be at least partially immersed into the bath where any undesirable material may be removed or cleaned or the energy may be used for other purposes such as removing air bubbles from the nozzle.

20 As shown in Fig. 4, part of the unit involves a source of vibrating energy, or vibration generator or energy converter (1), available from a variety of suppliers as would be known to those of ordinary skill in the art. This generator may develop a variety of frequencies of selected or varying amplitudes designed to optimally excite the probe ( that is for coupling oscillations to the exterior of the nozzle body that has specific selectable parameters such as a cleaning  
25 parameter, a gas dislocations parameter, or particle disintegration parameter, or sperm cell sorting, or alternately are chosen by sweeping a range of oscillations). In the preferred

embodiment, the vibration generator will have a amplitude and/or frequency adjustment or oscillation variation element or oscillation selector element which allows the operator to set or select the desired power level or sweep a range of oscillations prior to or during use (this can be critical as at least some particles and gas will have oscillation parameters that are highly dependant on flow cytometer operating conditions). The vibration generator or energy source or driver system (1) may be connected to a flexible cable or transfer element (2), as shown in Fig. 4, which conducts the electrical signals to an energy converter or oscillation system (3). The cable or transfer element may be flexible to allow the user to move the energy converter to the using area and of sufficient length to not require moving the vibration generator. The energy converter (3) turns the electrical energy from the vibration generator or drive system or energy source into mechanical energy of vibration or mechanical oscillations and can be connected to the attachment end (5) of the probe or portable device (4). The energy converter may in turn be connected to a mechanically isolated receptacle so that the energy converter may be hand held. In the preferred embodiment, the attachment end of the probe may be circular in cross section and has a female thread or joining element in it which allows the probe to be attached to the energy converter. The attachment end (5) of the probe may be circular to eliminate any thin walled sections of the probe which might be susceptible to cracking from stresses caused by the axial vibration of the probe. As would be known to those with skill in the art, the probe (4) is tuned by varying the dimensions of or selecting or sweeping the frequency of the vibration generator (1). In one embodiment for a cytometer nozzle, the probe may have an overall length of approximately 4-5 inches. The activating end (6) of the probe having the cavity or surface configured to the exterior surface of the flow cytometer nozzle or surface configured to cup a nozzle tip (7) may be approximately 0.5 inches high and approximately 0.3 inches wide. The cavity itself can be adjusted for a variety of nozzles and could be a hole approximately 0.25 inches in diameter and slightly less than the 0.5 inches height of the probe and can have or be a self alignment element for self alignment with the nozzle surface or a plurality interchange portable members with surfaces configured to approximately match portions of the exterior of the nozzle surface which may be attached and detached with a joining element.

#### Probe Material

In the preferred embodiment, the probe (4) may be constructed of titanium. This material

transmits the energy developed by the energy converter (3) efficiently. Further, it has sufficient stiffness to allow the probe to reflect the vibration energy back to the converter and develop various modes of vibration along the axis of the probe. This attribute allows the probe to be optimized such that sufficient energy is developed in the cavity (7), allowing the media in the cavity to be vibrationally excited to an optimum amount which effectively cleans the nozzle orifice while substantially maintaining the media in the cavity or in conjunction with a fluid retaining element. This material further has the advantage of not easily oxidizing or corroding when presented to saline and other fluids commonly used in conjunction with cytometers. This material is commonly used to make ultrasonic vibration probes by the manufacturers of such devices which are employed to do functions such as ultrasonic welding and forming of material.

In the preferred embodiment, the user would determine that the device is needed for a debubbling or unclogging operation and would fill the probe cavity with a cleaning media. This media may be water, saline, or other fluid, compatible with cytometers. It may also be a gel or solid which might remain in the cavity with some stability. Naturally, it could be a variety of other media, including a granular or even a solid media in appropriate instances. After filling the cavity (7) in the probe (4) while holding the energy converter (3) horizontally with the cavity facing upward, the operator could switch on the vibration generator and set or select or variably sweep the power level to the desired setting. The operator could then hold or hand hold the converter such that the nozzle orifice or nozzle exterior is at least partially immersed by the media or oscillation coupling element in the cavity and also adjoins at least part of the interior surface of the nozzle. The operator could hold the energy converter in this position for a time period such as a few seconds. While doing this operation the fluid lines going into the nozzle could remain pressurized. A liquid evacuation element could remove liquid from the cup so that the flow cytometer could be operated while coupled to the portable member. The operator could then move the converter such that the probe is not obstructing the normal spray path of the nozzle. The operator could then ascertain whether the nozzle was spraying normally or whether all air bubbles had been removed, and if not, repeat the operation.

In the preferred embodiment, the source of vibratory energy, the vibration generator (1), flexible cable (2), and energy converter (3) together may be provided as a readily available, off the shelf component to reduce costs.



Another embodiment is that of a cavity or cup or energy converter which is designed to be part of an instrument or product. This may be accomplished by using a first driver system for drop formation operation and a second driver circuit to drive the same drop formation oscillation system at different selected oscillation parameters or sweep a range of oscillations parameters so as to provide gas dislocation, particle disintegration, and cleaning parameters. Alternately, a second oscillation system driven by the second driver system could be employed. As shown in Fig. 7, the cavity (7) and probe or portable member (4) may be attached to a moving member or automated movement which could be moved to an area near the nozzle for any unclogging or debubbling operations and then moved out of the way. As would be known to those with skill in the art, such an arrangement could be mounted to the cytometer or some adjacent surface. It could be retractably placed at an indexed position to engage the cavity with the nozzle and then removed after attempting the declogging or debubbling. Such an arrangement could include hydraulic positioning, electromechanical positioning (such as by sensors, slides, limit switches and so forth). The embodiment could be actuated or triggered by an activation element manually or independant of flow cytometer operation conditions by an operator or when a declogging situation is noticed. Alternatively, it could be actuated automatically or in response to flow cytometer conditions when a sensor senses a declogging situation, such as by a reduced flow, an aberration in the flow direction, and so forth. Also as shown in Fig. 7, the probe (4) can be of a variety of shapes or a plurality of interchangeable tools as might be appropriate to the particular configuration and purposes.

Another embodiment involves the use of a more solid transfer of the vibration energy to the nozzle such as through the probe or energy converter itself or through a solid media or compressible element with a three-dimension surface in or on the probe or energy converter. The vibrating object may be placed against the nozzle which may transfer vibratory energy to the nozzle which may be used for air bubble removal or excitation of the fluid inside the nozzle in such a way as to unclog, or to clean the nozzle.

An alternative embodiment, shown in Fig. 8, includes a trap or droplet shield (12) for media which may be displaced from the cavity when the nozzle is placed into the cavity. These materials, if not trapped, could land on high voltage components below the nozzle or on optical components or analysis system which acts at least in part as a result of events within the free fall

area near the nozzle. The embodiment shown in Fig. 8 allows for a system and method of trapping these media before they become a problem. Of course, other embodiments could be employed to accomplish the same function.

5 In addition, it should be understood that, in the claims and in the application, the term “comprising” is meant to have an inclusive meaning rather than an exclusive one. It should be interpreted in its most expansive form so as to afford the applicant the broadest coverage legally permissible. Therefore, in countries, such as Australia, this term is not intended to have an exclusive, or more limited, meaning.

The discussion included in this application is intended to serve as a basic description.  
10 The reader should be aware that the specific discussion may not explicitly describe all embodiments possible; many alternatives are implicit. The marketplace and manufacturing concerns may dictate the appropriate embodiments for the present invention. Particularly with respect to the discussion, it should be understood that a number of changes may be made without departing from the essence of the present invention. In this regard, it is intended that such  
15 changes — to the extent that they substantially achieve the same results in substantially the same way — will still fall within the scope of the present invention. It also may not fully explain the generic nature of the invention and may not explicitly show how each feature or element can actually be representative of a broader function or of a great variety of alternative or equivalent elements. Again, these are implicitly included in this disclosure. Where the invention is  
20 described in device-oriented terminology, each element of the device implicitly performs a function. Apparatus discussions or claims may not only be included for the device described, but also method or process claims may be included to address the functions the invention and each element performs. Although the methods related to the system are being included in various detail, only an initial discussion directed toward the declogging/debubbling device have been  
25 included. Naturally, that discussion could have some application to the various other methods and apparatus discussed throughout the disclosure. This is particularly true for the present invention since its basic concepts and understandings may be broadly applied. Neither the description nor the terminology is intended to limit the scope of the claims.

It should be understood that a variety of changes may be made without departing from

the essence of the invention. Such changes are also implicitly included in the description. They still fall within the scope of this invention. A broad disclosure encompassing both the explicit embodiment(s) shown, the great variety of implicit alternative embodiments, and the broad methods or processes and the like are encompassed by this disclosure.

5 In addition, each of the various elements of the invention and claims may also be achieved in a variety of manners. This disclosure should be understood to encompass each such variation, be it a variation of an embodiment of any apparatus embodiment, a method or process embodiment, or even merely a variation of any element of these. Particularly, it should be understood that as the disclosure relates to elements of the invention, the words for each element  
10 may be expressed by equivalent apparatus terms or method terms — even if only the function or result is the same. Such equivalent, broader, or even more generic terms should be considered to be encompassed in the description of each element or action. Such terms can be substituted where desired to make explicit the implicitly broad coverage to which this invention is entitled. As but one example, it should be understood that all action may be expressed as a means for  
15 taking that action or as an element which causes that action. Similarly, each physical element disclosed should be understood to encompass a disclosure of the action which that physical element facilitates. Regarding this last aspect, the disclosure of a "vibration generator" should be understood to encompass disclosure of the act of "vibrating" — whether explicitly discussed or not — and, conversely, were there only disclosure of the act of "vibrating" such a disclosure  
20 should be understood to encompass disclosure of a "vibration generator" or a "vibrator." Such changes and alternative terms are to be understood to be explicitly included in the description.

Any references such as patents mentioned in the application for this patent as well as any references listed in any information disclosure filed with the application are hereby incorporated by reference; however, to the extent statements might be considered inconsistent with the  
25 patenting of this/these invention(s) such statements are expressly not to be considered as made by the applicant(s). Finally, it should also be understood that as to the claims the various combinations and permutations of each of the claims are possible.

**VI. CLAIMS**

What is claimed is:

1. A portable oscillating device for a flow cytometer which oscillates an exterior surface of a flow cytometer nozzle, comprising:
  - 5 a. a source of energy;
  - b. a transfer element coupled to said source of energy;
  - c. an energy converter coupled to said transfer element which creates mechanical oscillations;
  - 10 d. a portable member configured so as to mechanically couple said mechanical oscillations to said exterior surface of said flow cytometer nozzle.
2. A portable oscillating device for a flow cytometer which oscillates an exterior surface of a flow cytometer nozzle as described in claim 1 and further comprising a mechanically isolated receptacle connected to said portable member.
- 15 3. A portable oscillating device for a flow cytometer which oscillates an exterior surface of a flow cytometer nozzle as described in claim 2 wherein said mechanically isolated receptacle connected to said portable member is hand held.

4. A portable oscillating device for a flow cytometer which oscillates an exterior surface of a flow cytometer nozzle as described in claim 2 or 3 and further comprising a self alignment guide integral to said portable member which allows said portable member to self align with said exterior surface of said flow cytometer nozzle.
5. A portable oscillating device for a flow cytometer which oscillates an exterior surface of a flow cytometer nozzle as described in claim 3 and further comprising a compressible coupling element affixed to said portable member which has at least one three dimensional surface.
6. A portable oscillating device for a flow cytometer which oscillates an exterior surface of a flow cytometer nozzle as described in claim 3 and further comprising a cup surface configured to cup a nozzle tip of said flow cytometer nozzle.
7. A portable oscillating device for a flow cytometer which oscillates an exterior surface of a flow cytometer nozzle as described in claim 6 and further comprising an oscillation coupling element held within said cup surface configured to cup said exterior surface of said nozzle tip of said flow cytometer nozzle.
8. A portable oscillating device for a flow cytometer which oscillates an exterior surface of a flow cytometer nozzle as described in claim 7 wherein said oscillation coupling element held within said cup surface configured to cup said exterior surface of said nozzle tip of said flow cytometer nozzle comprises a solid material.

9. A portable oscillating device for a flow cytometer which oscillates an exterior surface of a flow cytometer nozzle as described in claim 7 wherein said oscillation coupling element held within said cup surface configured to cup said exterior surface of said nozzle tip of said flow cytometer nozzle comprises a liquid material.
- 5 10. A portable oscillating device for a flow cytometer which oscillates an exterior surface of a flow cytometer nozzle as described in claim 9 and further comprising a fluid retaining element with a first side affixed to said portable member and a second side which conforms to said exterior of said flow cytometer nozzle with said first side and said second side and said cup surface configured to cup said exterior surface of said flow cytometer nozzle.
- 10 11. A portable oscillating device for a flow cytometer which oscillates an exterior surface of a flow cytometer nozzle as described in claim 10 and further comprising a liquid evacuation element which connects said cup surface configured to cup said exterior surface of said flow cytometer with said portable surface of said portable member to remove liquid from said cup surface configured to cup said exterior surface of said nozzle tip of said flow cytometer nozzle.
- 15 12. A portable oscillating device for a flow cytometer which oscillates an exterior surface of a flow cytometer nozzle as described in claim 3 and further comprising a joining element with a first half and a second half wherein said first half of said joining element and said second half of said joining element removably join.
- 20

13. A portable oscillating device for a flow cytometer which oscillates an exterior surface of a flow cytometer nozzle as described in claim 12 and further comprising a plurality of interchangeable portable members wherein each said interchangeable portable member has a nozzle exterior matching surface which mechanically couples with a corresponding matching surface of said exterior surface of said flow cytometer nozzle.
14. A portable oscillating device for a flow cytometer which oscillates an exterior surface of a flow cytometer nozzle as described in claims 1, 3, 6, 9, 10, or 11 and further comprising a oscillation selection element which drives said energy converter at one of multiple selectable oscillation parameter.
15. A portable oscillating device for a flow cytometer which oscillates an exterior surface of a flow cytometer nozzle as described in claim 14 where in said oscillation selection element drives said energy converter at a selectable oscillation parameter which corresponds to a nozzle aperture cleaning parameter.
16. A portable oscillating device for a flow cytometer which oscillates an exterior surface of a flow cytometer nozzle as described in claim 14 where in said oscillation selection element drives said energy converter at a selectable oscillation parameter which corresponds to a particle disintegration parameter.
17. A portable oscillating device for a flow cytometer which oscillates an exterior surface of a flow cytometer nozzle as described in claim 14 wherein said oscillation selection element drives said energy converter at said selectable oscillation parameter which

corresponds to a gas dislocation parameter.

18. A portable oscillating device for a flow cytometer which oscillates an exterior surface of a flow cytometer nozzle as described in claims 1, 3, 6, 9, 10, or 11 and further comprising a an oscillation variation element which drives said energy converter over a range of oscillations.
19. A portable oscillating device for a flow cytometer which oscillates an exterior surface of a flow cytometer nozzle as described in claim 1, 3, 6, 9, 10, or 11 and further comprising an automated movement to which said mechanically isolated receptacle is responsive which couples said portable surface configured so as to mechanically couple said mechanical oscillations to said exterior surface of said flow cytometer nozzle with said exterior surface of said flow cytometer nozzle.
20. A portable oscillating device for a flow cytometer which oscillates an exterior surface of a flow cytometer nozzle as described in claim 19 and further comprises a activation circuit connected to said automated movement which activates said automated movement independent of flow cytometry operation conditions.
21. A portable oscillating device for a flow cytometer which oscillates an exterior surface of a flow cytometer nozzle as described in claim 19 wherein said activation circuit connected to said automated movement which activates said automated movement in response to said flow cytometer operation conditions.



## 22. A drop flow cytometer system, comprising:

- a. a portable oscillating device as described in claims 1, 3, 6, 9, 10, or 11;
- b. a sheath fluid;
- 5 c. a nozzle body within which at least a portion of said sheath fluid is contained;
- d. a sample introduction element contained within said nozzle body;
- e. a oscillation system to which said sheath fluid is responsive and which acts to create droplets;
- 10 f. a first driver system to which said oscillation system is responsive;
- g. a second driver system to which said oscillation system is responsive;
- h. a free fall area within which said droplets form and fall;
- i. an analysis system acting at least in part as a result of events within said free fall area; and
- 15 j. a sort system responsive to said analysis system which acts upon said droplets in said free fall area.

- 23. A portable oscillating device for a flow cytometer which oscillates an exterior surface of a flow cytometer nozzle as described in claims 22 and further comprising a second energy converter which creates mechanical oscillations coupled to said exterior surface of said flow cytometer nozzle.
- 20

24. A portable oscillating device for a flow cytometer which oscillates an exterior surface of a flow cytometer nozzle as described in claim 22 and further comprising a droplet shield coupled to said drop flow cytometer system between said exterior surface of said flow cytometer nozzle that forms droplets and an instrument surface of said flow cytometer system surface.
- 5
25. A drop flow cytometer system, comprising:
- a. a portable oscillating device as described in claim 14;
  - b. a sheath fluid;
  - c. a nozzle body within which at least a portion of said sheath fluid is contained;
  - d. a sample introduction element contained within said nozzle body;
  - e. a oscillation system to which said sheath fluid is responsive and which acts to create droplets;
  - f. a first driver system to which said oscillation system is responsive;
  - g. a second driver system to which said oscillation system is responsive;
  - h. a free fall area within which said droplets form and fall;
  - i. an analysis system acting at least in part as a result of events within said free fall area; and
  - j. a sort system responsive to said analysis system which acts upon said
- 10
- 15

droplets in said free fall area.

26. A portable oscillating device for a flow cytometer which oscillates an exterior surface of a flow cytometer nozzle as described in claims 25 and further comprising a second energy converter which creates mechanical oscillations coupled to said exterior surface of said flow cytometer nozzle.
27. A portable oscillating device for a flow cytometer which oscillates an exterior surface of a flow cytometer nozzle as described in claim 25 and further comprising a droplet shield coupled to said drop flow cytometer system between said exterior surface of said flow cytometer nozzle that forms droplets and an instrument surface of said flow cytometer system surface.
28. A drop flow cytometer system, comprising:
  - a. a portable oscillating device as described in claim 18;
  - b. a sheath fluid;
  - c. a nozzle body within which at least a portion of said sheath fluid is contained;
  - d. a sample introduction element contained within said nozzle body;
  - e. a oscillation system to which said sheath fluid is responsive and which acts to create droplets;

- 5
- f. a first driver system to which said oscillation system is responsive;
  - g. a second driver system to which said oscillation system is responsive;
  - h. a free fall area within which said droplets form and fall;
  - i. an analysis system acting at least in part as a result of events within said free fall area; and
  - j. a sort system responsive to said analysis system which acts upon said droplets in said free fall area.
- 10
29. A portable oscillating device for a flow cytometer which oscillates an exterior surface of a flow cytometer nozzle as described in claims 28 and further comprising a second energy converter which creates mechanical oscillations coupled to said exterior surface of said flow cytometer nozzle.
- 15
30. A portable oscillating device for a flow cytometer which oscillates an exterior surface of a flow cytometer nozzle as described in claim 28, 29, or 30 and further comprising a droplet shield coupled to said drop flow cytometer system between said exterior surface of said flow cytometer nozzle that forms droplets and an instrument surface of said flow cytometer system surface.
31. A drop flow cytometer system, comprising:
- a. a portable oscillating device as described in claim 21;

- b. a sheath fluid;
- c. a nozzle body within which at least a portion of said sheath fluid is contained;
- d. a sample introduction element contained within said nozzle body;
- 5 e. a oscillation system to which said sheath fluid is responsive and which acts to create droplets;
- f. a first driver system to which said oscillation system is responsive;
- g. a second driver system to which said oscillation system is responsive;
- h. a free fall area within which said droplets form and fall;
- 10 i. an analysis system acting at least in part as a result of events within said free fall area; and
- j. a sort system responsive to said analysis system which acts upon said droplets in said free fall area.

15 32. A portable oscillating device for a flow cytometer which oscillates an exterior surface of a flow cytometer nozzle as described in claims 31 and further comprising a second energy converter which creates mechanical oscillations coupled to said exterior surface of said flow cytometer nozzle.

33. A portable oscillating device for a flow cytometer which oscillates an exterior surface of

a flow cytometer nozzle as described in claim 31 and further comprising a droplet shield coupled to said drop flow cytometer system between said exterior surface of said flow cytometer nozzle that forms droplets and an instrument surface of said flow cytometer system surface.

- 5      34.    A drop flow cytometer system, comprising:
- a.      a sheath fluid;
  - b.      a nozzle body within which at least a portion of said sheath fluid is contained;
  - c.      a sample introduction element contained within said nozzle body;
  - 10      d.      a oscillation system to which said sheath fluid is responsive and which acts to create droplets;
  - e.      a first driver system to which said oscillation system is responsive;
  - f.      a second driver system to which said oscillation system is responsive;
  - g.      a free fall area within which said droplets form and fall;
  - 15      h.      an analysis system acting at least in part as a result of events within said free fall area; and
  - i.      a sort system responsive to said analysis system which acts upon said droplets in said free fall area.

35. A drop flow cytometer system as described in claim 34 wherein said first driver system and said second driver system have different oscillation parameters.
36. A drop flow cytometer system as described in claim 35 wherein said sheath fluid is responsive to said second driver system.
- 5 37. A drop flow cytometer system as described in claim 35 and further comprising a oscillation parameter selector which establishes said oscillation parameters.
38. A drop flow cytometer system as described in claim 37 wherein said oscillation parameter selector element establishes said second driver system parameter at a nozzle cleaning parameter.
- 10 39. A drop flow cytometer system as described in claim 37 wherein said oscillation parameter selector element establishes said second driver system at a gas dislocation parameter.
40. A drop flow cytometer system as described in claim 37 wherein said oscillation parameter selector element establishes said second driver system at a particle disintegration parameter.
- 15

41. A drop flow cytometer system as described in claim 34 wherein said nozzle body has an exterior surface and wherein said oscillation system comprises:
- a. a first oscillation system driven by said first driver system;
  - b. a second oscillation system driven by said second driver system;
  - 5 c. a second oscillation system coupling element having an exterior oscillation surface coupled to said exterior surface of said nozzle body.
42. A drop flow cytometer system as described in claim 41 wherein said exterior surface of said second oscillation system coupling element is configured to complement said exterior surface of said nozzle body.
- 10 43. A drop flow cytometer system as described in claim 42 wherein said second oscillation system coupling element comprises a fluidic oscillation coupling element.
44. A drop flow cytometer system as described in claim 43 wherein said nozzle body has a nozzle aperture and wherein said fluidic oscillation coupling element couples said second oscillation system to said nozzle aperture of said nozzle body.
- 15 45. A drop flow cytometer system as described in claim 44 wherein said fluidic oscillation coupling element adjoins at least part of an internal surface of said nozzle aperture surface.



46. A drop flow cytometer system as described in claim 41 and further comprising said oscillation parameter selector which establishes said oscillation parameters.

47. A drop flow cytometer system as described in claim 46 wherein said oscillation parameter selector element establishes said second driver system at a nozzle cleaning parameter.

48. A drop flow cytometer system as described in claim 46 wherein said oscillation parameter selector element establishes said second driver system at a gas dislocation parameter.

49. A drop flow cytometer system as described in claim 46 wherein said oscillation parameter selector element establishes said second driver system at a particle disintegration parameter.

50. A drop flow cytometer system as described in claim 41 and further comprising an oscillation variation element to which said oscillation system is responsive.

51. A drop flow cytometer system with a dual oscillation flow cytometer nozzle device as described in claim 37 or 50 wherein said oscillation system changes independent of drop flow cytometer operating conditions.

52. A drop flow cytometer system with a dual oscillation flow cytometer nozzle device as described in claim 37 or 50 wherein said oscillation system changes automatically changes in response to drop flow cytometer operating conditions.

5 53. A drop flow cytometer system with a dual oscillation flow cytometer nozzle device as described in claim 34 or 41 and further comprising an instrument protection shield which surrounds said nozzle body when said second driver system is activated.

54. A fluidic oscillation system for a flow cytometer which oscillates a flow cytometer nozzle exterior surface, comprising:

10 a. an energy source;

b. a energy transfer element coupled to said source of energy;

c. a energy converter connected to said energy transfer element and which creates mechanical oscillations; and

15 d. a fluidic oscillation coupling element which is responsive to said energy converter and which is fluidicly coupled to said flow cytometer nozzle exterior surface.

55. A flow cytometer system as described in claim 46 and further comprising:

a. a sheath fluid;

- 5
- b. a nozzle body within which at least a portion of said sheath fluid is contained;
  - c. a sample introduction element contained within said nozzle body;
  - d. a oscillation system to which said fluidic oscillation coupling element is responsive;
  - e. a free fall area below said flow cytometer nozzle exterior surface;
  - f. an analysis system acting at least in part as a result of events within said free fall area; and
  - g. a sort system responsive to said analysis system.

10 56. A flow cytometer system as described in claim 55 and further comprising a flow cytometer nozzle interior surface and wherein said fluidic oscillation coupling element adjoins at least part of said flow cytometer interior surface

15 57. A flow cytometer system as described in claim 57 and further comprising a oscillation parameter selection element which operates said energy converter at selectable oscillation parameters.

58. A flow cytometer system as described in claim 57 wherein said oscillation parameter selection element operates said energy converter at said selectable oscillation parameters corresponding to a nozzle aperture cleaning parameter.

59. A flow cytometer system as described in claim 57 wherein said oscillation parameter selection element operates said energy converter at said selectable oscillation parameters corresponding to a gas dislocation parameter.
60. A flow cytometer system as described in claim 57 wherein said oscillation parameter selection element operates said energy converter at said selectable oscillation parameters corresponding to a particle disintegration parameter.
61. A flow cytometer system as described in claim 57 wherein said oscillation parameter selection element operates said energy converter at said selectable oscillation parameters corresponding to a sperm break-up parameter.
62. A flow cytometer system as described in claim 54 and further comprising a oscillation variation element which operates said energy converter throughout an range of at least one oscillation parameter useful to the operation of said flow cytometer system.
63. A oscillation system for a flow cytometer, comprising:
- a. an energy source;
  - b. a energy transfer element coupled to said energy source;
  - c. a energy converter connected to said energy transfer element which outputs mechanical oscillations; and

- d. an oscillation variation system which operates said energy converter throughout a range of at least one oscillation parameter.

64. A flow cytometer system as described in claim 55 and further comprising:

- a. a sheath fluid;
- b. a nozzle body within which at least a portion of said sheath fluid is contained;
- c. a sample introduction element contained within said nozzle body;
- d. a oscillation system which is responsive to said oscillation variation system;
- e. a free fall area below said flow cytometer nozzle exterior surface;
- f. an analysis system acting at least in part as a result of events within said free fall area; and
- g. a sort system responsive to said analysis system.

5

10

15

65. A flow cytometer system as described in claim 63 wherein said nozzle body has an interior surface and wherein said oscillation variation selection system selects a cleaning oscillation to remove adherents from said interior surface of said nozzle body.

66. A flow cytometer system as described in claim 65 wherein said oscillation variation selection system selects a gas dislocation oscillations to dislocate gas entrapped within said nozzle body.
- 5 67. A flow cytometer system as described in claim 65 wherein said oscillation variation selection system selects a particle disintegration oscillation to disintegrate particles entrapped within said nozzle body.
68. A method of flow cytometry, comprising the steps of:
- a. providing a flow cytometry apparatus having an exterior surface;
  - b. introducing a sample within said flow cytometry apparatus;
  - 10 c. conducting flow cytometry through action of said flow cytometry apparatus;
  - d. engaging said exterior surface of said flow cytometry apparatus by a portable member;
  - e. 15 creating oscillations within said flow cytometry apparatus through action of said portable member;
  - f. disengaging said portable member from said exterior surface of said flow cytometry apparatus; and
  - g. continuing to conduct flow cytometry through action of said flow cytometry apparatus.

69. A method of flow cytometry as described in claim 68 and further comprising mechanically isolating said portable member.

70. A method of flow cytometry as described in claim 69 and further comprising the step of holding said receptacle in a hand to removably couple said mechanical oscillations to said exterior surface of said flow cytometer nozzle.

71. A method of flow cytometry as described in claim 70 and further comprising the step of compressing a coupling element to said portable surface of said portable member.

72. A method of flow cytometry as described in claim 71 and further comprising the step of cupping a surface configured to approximate the exterior dimensions of said exterior surface of said flow cytometer apparatus near said exterior surface of said flow cytometer apparatus.

73. A method of flow cytometry as described in claim 72 and further comprising the step of oscillating said exterior surface of said flow cytometer apparatus with an oscillation coupling element held within said cup surface.

74. A method of flow cytometry as described in claim 73 wherein said step of oscillating

said exterior surface of said flow cytometer apparatus with an oscillation coupling element held within said cup surface comprises using a solid oscillation coupling element.

- 5 75. A method of flow cytometry as described in claim 73 wherein said step of oscillating said exterior surface of said flow cytometer apparatus with an oscillation coupling element held within said cup surface comprises the use of a liquid oscillation coupling element.
- 10 76. A method of flow cytometry as described in claim 75 wherein said flow cytometry apparatus has an interior surface and further comprising the step of fluidically coupling said oscillations to said interior surface of said flow cytometry apparatus.
77. A method of flow cytometry as described in claim 75 and further comprising the step of draining said surface configured to cup said exterior surface of said flow cytometer of fluid.
- 15 78. A method of flow cytometry as described in claim 73 and further comprising the step of retaining said oscillation coupling element within said portable member cupping said exterior surface of said flow cytometer apparatus with a fluid retaining element having a first side affixed to said portable member and a second side which conforms to said exterior of said flow cytometer apparatus with said first side and said second side and said surface configured to cup said exterior surface of said flow cytometer apparatus.



79. A method of flow cytometry as described in claim 68, 69, 70, 72, 73 or 76 and further comprising the step of selecting said mechanical oscillations created by said energy converter by selecting said parameter from an oscillation selection element.
- 5 80. A method of flow cytometry as described in claim 79 and further comprising the step of disintegrating a particle within said flow cytometer apparatus when said portable member is cupping said exterior surface.
- 10 81. A method of flow cytometry as described in claim 79 and further comprising the step of dislocating a gas within said flow cytometer apparatus when said portable member is cupping said exterior surface of said flow cytometer apparatus by selecting a gas dislocation oscillation from said oscillation selection element.
82. A method of flow cytometry as described in claims 68, 69, 70, 72, 73, or 76 and further comprising the step of sweeping a range of oscillations.
- 15 83. A method of flow cytometry as described in claims 68, 69, 70, 71, 72, 73, 76, or 78 and further comprising the step of moving said portable member with an automated moving system.
84. A method of flow cytometry as described in claims 79 and further comprising the step of moving said portable member with an automated moving system.

85. A method of flow cytometry as described in claims 82 and further comprising the step of moving said portable member with an automated moving system.
86. A method of flow cytometry as described in claim 83 and further comprising the step of manually activating said automated moving system.
- 5 87. A method of flow cytometry as described in claim 83 and further comprising the step of automatically activating said automated moving system in response to preselected flow cytometer operating parameters.
88. A flow cytometer system, comprising:
- a. a flow cytometry apparatus;
  - 10 b. an energy source;
  - c. a energy transfer element coupled to said energy source; and
  - d. a de-bubbling energy converter connected to said energy transfer element which outputs mechanical oscillations selected to have a de-bubbling oscillation parameter corresponding to gas dislocation which dislocates gas bubbles with said de-bubbling oscillation parameter from within said  
15 flow cytometer apparatus.

89. A method of flow cytometry, of:

- a. providing a flow cytometry apparatus having an exterior surface;
- b. providing a source of energy;
- c. transferring said energy through a transfer element;
- 5 d. converting said energy with a energy converter which outputs mechanical oscillations;
- e. introducing a sample within said flow cytometry apparatus;
- f. conducting flow cytometry through action of said flow cytometry apparatus;
- 10 g. creating oscillations in the vicinity of said flow cytometry apparatus; and
- h. fluidicly coupling said oscillations to said exterior surface of said flow cytometry apparatus.

90. A method of flow cytometry as described in claim 89 wherein said step of fluidicly coupling said oscillations to said exterior surface of said flow cytometry apparatus comprises the step of cupping a cup surface configured to approximate the exterior dimensions of said exterior surface of said flow cytometer apparatus near said exterior surface of said flow cytometer apparatus.

15

91. A method of flow cytometry as described in claim 89 or 90 wherein said step of fluidically coupling said oscillations to said exterior surface of said flow cytometry apparatus comprises using a solid.
92. A method of flow cytometry as described in claim 89 or 90 wherein said step of fluidically coupling said oscillations to said exterior surface of said flow cytometry apparatus comprises using a liquid.
93. A method of flow cytometry as described in claim 92 wherein said step of fluidically coupling said oscillations to said exterior surface of said flow cytometry apparatus comprises the step of fluidically coupling said oscillations to said interior surface of said flow cytometer apparatus.
94. A method of flow cytometry as described in claim 93 and further comprising the step of draining said surface configured to cup said exterior surface of said flow cytometer of fluid.
95. A method of flow cytometry as described in claim 89, 90, or 93 and further comprising the step of retaining said oscillation coupling element within said portable member cupping said exterior surface of said flow cytometer apparatus with a fluid retaining element having a first side affixed to said portable member and a second side which conforms to said exterior of said flow cytometer apparatus with said first side and said second side and said surface configured to cup said exterior surface of said flow cytometer apparatus.

96. A method of flow cytometry as described in claim 89, 90, 93, or 94 and further comprising the step of selecting said mechanical oscillations created by said energy converter by selecting said parameter from an oscillation selection element.
97. A method of flow cytometry as described in claim 96 and further comprising the step of disintegrating a particle within said flow cytometer apparatus when said portable member is cupping said exterior surface.
98. A method of flow cytometry as described in claim 96 and further comprising the step of dislocating a gas within said flow cytometer apparatus when said portable member is cupping said exterior surface of said flow cytometer apparatus by selecting a gas dislocation oscillation from said oscillation selection element.
99. A method of flow cytometry as described in claim 89, 90, 93, or 94 and further comprising the step of sweeping a range of oscillations.
100. A method of flow cytometry as described in claim 89, 90, 93, or 94 and further comprising the step of moving said portable member with an automated moving system.
101. A method of flow cytometry as described in claim 96 and further comprising the step of sweeping a range of oscillations.

102. A method of flow cytometry as described in claim 96 and further comprising the step of moving said portable member with an automated moving system.

103. A method of flow cytometry as described in claim 100 and further comprising the step of manually activating said automated moving system.

5 104. A method of flow cytometry as described in claim 100 and further comprising the step of automatically activating said automated moving system in response to preselected flow cytometer operating parameters.

105. A method of flow cytometry, comprising the steps of:

- a. providing a flow cytometry apparatus;
- 10 b. providing a source of energy;
- c. transferring said energy through a transfer element;
- d. converting said energy with an energy converter which creates mechanical oscillations;
- 15 e. selecting a de-bubbling oscillation parameter corresponding to gas dislocation which dislocates gas bubbles with said de-bubbling oscillation parameter from within said flow cytometer apparatus;
- f. creating de-bubbling oscillations within said flow cytometry apparatus

using said de-bubbling oscillation parameter;

- g. introducing a sample within said flow cytometry apparatus; and
- h. conducting flow cytometry through action of said flow cytometry apparatus.

- 5      106. A method of flow cytometry as described in claim 105 wherein said step of creating de-bubbling oscillations comprises the step of sweeping a range of oscillations.

107. A method of flow cytometry, comprising the steps of:

- a. establishing a sheath fluid in a nozzle body;
- b. introducing a sample within said nozzle body;
- 10      c. entraining said sample within said sheath fluid;
- d. flowing said sample and said sheath fluid out of said nozzle body and into a free fall area;
- e. creating a first oscillation mode to which said sheath fluid is responsive as said sheath fluid flows out of said nozzle body;
- 15      f. creating drops from said sheath fluid within said free fall area as a result of said first oscillation mode;
- g. analyzing events within said free fall area;

- h. sorting said drops within said free fall area as a result of said step of analyzing events within said free fall area;
- i. temporarily establishing a second oscillation mode within said nozzle body; and
- 5 j. continuing to conduct flow cytometry through action of said flow cytometry apparatus.

108. A method of flow cytometry, comprising the steps of:

- a. providing a flow cytometry apparatus;
- b. introducing a sample within said flow cytometry apparatus;
- 10 c. conducting flow cytometry through action of said flow cytometry apparatus;
- d. creating oscillations in the vicinity of said flow cytometry apparatus; and
- e. sweeping said oscillations throughout a range of at least one oscillation parameter.

- 15 109. A method of flow cytometry as described in claim 108 wherein said flow cytometry apparatus is a drop flow cytometry apparatus.



1/8




FIG.1

2/8




FIG.2

3/8




FIG.3

4/8




FIG. 4

5/8




FIG.5

6/8




FIG. 6

7/8




FIG. 7

8/8




FIG. 8



Express Mail No: EL627894581US

Attorney Docket: XY-Sonic-USNP

IN THE UNITED STATES PATENT AND  
TRADEMARK OFFICE

In Re the Application of: Kristopher S. Buchanan, Lisa Herickhoff, George Seidel, George  
C. Malachowski, Matthias J.G. Ottenberg, Douglas H. Ferguson

Serial Number: (original US) 60/075,612 (new) \_\_\_\_\_  
(PCT) PCT/US99/03638

Filed: (original US) 20 February 1998 (new) \_\_\_\_\_  
(PCT) 19 February 1999

For: A Vibratory System For A Sorting Flow Cytometer

Group Art Unit:


Examiner:

Assignee:

**POWER OF ATTORNEY**

I, Nigel M. Ferrey as President of Cytomation, Inc., hereby appoint Santangelo Law Offices, P.C., whose mailing address is 125 South Howes, Third Floor, Fort Collins, Colorado 80521, including Luke Santangelo, whose registration number before the United States Patent and Trademark Office is 31,997, Craig R. Miles, whose registration number before the United States Patent and Trademark Office is 45,954, and Chad C. Soliz, whose registration number before the United States Patent and Trademark Office is P-47,101, as Cytomation, Inc.'s attorney(s)/agent(s) to prosecute this application entitled "A Vibratory System For A Sorting Flow Cytometer" and to transact all business in the Patent Office connected therewith.

Dated this 8 day of August, 2000.

By:   
Nigel M. Ferrey as President of Cytomation, Inc.

Express Mail No: EL627894581US

Attorney Docket: XY-Sonic-USNP

**IN THE UNITED STATES PATENT AND  
TRADEMARK OFFICE**

In Re the Application of: Kristopher S. Buchanan, Lisa Herickhoff, George Seidel, George  
C. Malachowski, Matthias J.G. Ottenberg, Douglas H. Ferguson

Serial Number: (original US) 60/075,612 (new) \_\_\_\_\_  
(PCT) PCT/US99/03638

Filed: (original US) 20 February 1998 (new) \_\_\_\_\_  
(PCT) 19 February 1999

For: A Vibratory System For A Sorting Flow Cytometer

Group Art Unit:

Examiner:

Assignee:

**POWER OF ATTORNEY**

I, Dr. Mervyn Jacobson, President, hereby appoint Santangelo Law Offices, P.C., whose mailing address is 125 South Howes, Third Floor, Fort Collins, Colorado 80521, including Luke Santangelo, whose registration number before the United States Patent and Trademark Office is 31,997, Craig R. Miles, whose registration number before the United States Patent and Trademark Office is 45,954, and Chad C. Soliz, whose registration number before the United States Patent and Trademark Office is P-47,101, as XY's attorney(s)/agent(s) to prosecute this application entitled "A Vibratory System For A Sorting Flow Cytometer" and to transact all business in the Patent Office connected therewith.

Dated this 8 day of August, 2000.

By: \_\_\_\_\_

Dr. Mervyn Jacobson, President of XY, Inc.

Express Mail No: EL627894581US

Attorney Docket:XY-Sonic-USNP

**IN THE UNITED STATES PATENT AND  
TRADEMARK OFFICE**

In Re the Application of: Kristopher S. Buchanan, Lisa Herickhoff, George Seidel, George C. Malachowski, Matthias J.G. Ottenberg, Douglas H. Ferguson

Serial Number: (original US) 60/075,612 (new) \_\_\_\_\_  
(PCT) PCT/US99/03638

Filed: (original US) 20 February 1998 (new) \_\_\_\_\_  
(PCT) 19 February 1999

For: A Vibratory System For A Sorting Flow Cytometer

Group Art Unit:

Examiner:

Assignee:

**POWER OF ATTORNEY**

I, Arundee S. Pradhan, Director of Technology Transfer, on behalf of the Assignee, Colorado State University Research Foundation as agent for Colorado State University, hereby appoint Santangelo Law Offices, P.C., whose mailing address is 125 South Howes, Third Floor, Fort Collins, Colorado 80521, including Luke Santangelo, whose registration number before the United States Patent and Trademark Office is 31,997, Craig R. Miles, whose registration number before the United States Patent and Trademark Office is 45,954, and Chad C. Soliz, whose registration number before the United States Patent and Trademark Office is P-47,101, as my attorney(s)/agent(s) to prosecute this application entitled "A Vibratory System For A Sorting Flow Cytometer" and to transact all business in the Patent Office connected therewith.

Dated this 16<sup>th</sup> day of August, 2000.

By:



Arundee S. Pradhan, Director of Technology Transfer, on behalf of the Assignee, Colorado State University Research Foundation as agent for Colorado State University

09/622621

533 Rec'd PCT/PTO 18 AUG 2000

Express Mail No: EL627894581US

Attorney Docket: XY-Sonic-USNP

IN THE UNITED STATES PATENT AND  
TRADEMARK OFFICE

In Re the Application of: Kristopher S. Buchanan, Lisa Herickhoff, George Seidel, George C. Malachowski, Matthias J.G. Ottenberg, Douglas H. Ferguson

Serial Number: (original US) 60/075,612 (new) \_\_\_\_\_  
(PCT) PCT/US99/03638

Filed: (original US) 20 February 1998 (new) \_\_\_\_\_  
(PCT) 19 February 1999

For: A Vibratory System For A Sorting Flow Cytometer

Group Art Unit:

Examiner:

Assignee:

**CERTIFICATE OF EXPRESS MAILING**

I, Shannon Nation-Kammerer, hereby certify to the truth of the following items:

1. I am an employee of Santangelo Law Offices, P.C., 125 South Howes, Third Floor, Fort Collins, Colorado 80521.

2. I have this day deposited the attached Power of Attorney for Cytomation, Inc., XY, Inc. and Colorado State University through its agent Colorado State University Research Foundation with the United States Postal Service as "Express Mail" for mailing to the Assistant Commissioner of Patents, Box PCT, Washington, D.C. 20231.

Dated this 18 day of August, 2000.



Express Mail No: EL627894581US

Attorney Docket: XY-Sonic-USNP

**IN THE UNITED STATES PATENT AND  
TRADEMARK OFFICE**

In Re the Application of: Kristopher S. Buchanan, Lisa Herickhoff, George Seidel, George  
C. Malachowski, Matthias J.G. Ottenberg, Douglas H. Ferguson

Serial Number: (original US) 60/075,612 (new) \_\_\_\_\_  
(PCT) PCT/US99/03638

Filed: (original US) 20 February 1998 (new) \_\_\_\_\_  
(PCT) 19 February 1999

For: A Vibratory System For A Sorting Flow Cytometer

Group Art Unit:

Examiner:

Assignee:

**DECLARATION FOR PATENT APPLICATION**

This Declaration is made by Kristopher S. Buchanan, Lisa Herickhoff, George Seidel,  
George C. Malachowski, Matthias J.G. Ottenberg and Douglas H. Ferguson.

I, Kristopher S. Buchanan, hereby declare:

- I am a citizen of the United States of America and that my residence and mailing address  
is 4300 Shadowbrooke Court, Fort Collins, CO 80526.

I, Lisa Herickhoff, hereby declare:

- I am a citizen of the United States of America and that my residence and mailing address  
is 5123 E. County Road 52, Fort Collins, CO 80524.

I, George Seidel, hereby declare:

- I am a citizen of the United States of America and that my residence and mailing address  
is 3101 Arrowhead Road, LaPorte, CO 80535.

I, George C. Malachowski, hereby declare:

- I am a citizen of Australia and that my residence and mailing address is 1112 Remington  
Street, Fort Collins, CO 80524.

500 I, Matthias J.G. Ottenberg, hereby declare:

- I am a citizen of the United States of America and that my residence and mailing address is 3002 Indigo Court, Fort Collins, CO 80525. Co

600 I, Douglas H. Ferguson, hereby declare:

- I am a citizen of the United States of America and that my residence and mailing address is 37673 587th Avenue, Eden Valley, MN 55329. MN

We believe that we are the original, first, and inventors of the subject matter which is claimed and for which a patent is sought on the invention entitled "A Vibratory System For A Sorting Flow Cytometer", and

- as originally entitled " A Vibratory Unclogging Tool for Cytometer Nozzles" the specification of which was filed as United States Application Number 60/075,612, filed on February 20, 1998 (the "Original US Application"), and also
- as PCT Application Number PCT/US99/03638 filed on February 19, 1999, and designating the United States of America; this PCT Application being filed while the Original US Application was pending.

We hereby state that we have reviewed and understand the contents of the above-identified specifications, including the claims.

We hereby claim the benefit under Title 35, United States Code § 119, § 120, § 365 and otherwise of each of the above referenced foreign, United States and PCT patent application(s); there are no foreign applications having a filing date before that of the application(s) on which priority is claimed.

We acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56(a). Further, insofar as the subject matter of any claims of this application was not disclosed in the prior United States or PCT International application I acknowledge the duty to disclose information which is known to be material to patentability as defined in Title 37, Code of Federal Regulations § 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

We hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements are made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Date: 9/13/00

Kristopher S. Buchanan  
Kristopher S. Buchanan

UNITED STATES OF AMERICA    )  
STATE OF COLORADO            )ss.  
COUNTY OF LARIMER            )

SUBSCRIBED AND AFFIRMED OR SWORN to before me in the County of Larimer,  
State of Colorado, United States of America, by Kristopher S. Buchanan, this 13 day of  
September, 2000.

WITNESS my hand and official seal pursuant to the authority vested in me as a Notary Public  
by the State of Colorado.



My Commission Expires 07/15/2003

Shannon M. Nation-Kammerer  
Notary Public  
My Commission Expires: 7-15-2003

Date:

Sept 18, 2000  
Lisa Herickhoff


UNITED STATES OF AMERICA    )  
STATE OF COLORADO            )ss.  
COUNTY OF LARIMER            )

SUBSCRIBED AND AFFIRMED OR SWORN to before me in the County of Larimer,  
State of Colorado, United States of America, by Lisa Herickhoff, this 18 day of September,  
2000.

WITNESS my hand and official seal pursuant to the authority vested in me as a Notary Public  
by the State of Colorado.



My Commission Expires 07/15/2003

  
Notary Public  
My Commission Expires: 7-15-2003



Date:

Sept 12, 2000George Seidel  
George Seidel

UNITED STATES OF AMERICA )  
STATE OF COLORADO )ss.  
COUNTY OF LARIMER )

SUBSCRIBED AND AFFIRMED OR SWORN to before me in the County of Larimer,  
State of Colorado, United States of America, by George Seidel, this 12 day of September, 2000.

WITNESS my hand and official seal pursuant to the authority vested in me as a Notary Public  
by the State of Colorado.

Shannon M. Nation-Kammerer  
Notary Public  
My Commission Expires: 7-15-2003



My Commission Expires 07/15/2003

Date:

13th Sep '00

George C. Malachowski

UNITED STATES OF AMERICA )  
STATE OF COLORADO )ss.  
COUNTY OF LARIMER )

SUBSCRIBED AND AFFIRMED OR SWORN to before me in the County of Larimer,  
State of Colorado, United States of America, by George C. Malachowski, this 13 day of  
September, 2000.

WITNESS my hand and official seal pursuant to the authority vested in me as a Notary Public  
by the State of Colorado.



Notary Public

My Commission Expires: 7-15-2003


My Commission Expires 07/15/2003

Date: 9/13/00  
Matthias J.G. Ottenberg


UNITED STATES OF AMERICA )  
STATE OF COLORADO )ss.  
COUNTY OF LARIMER )

SUBSCRIBED AND AFFIRMED OR SWORN to before me in the County of Larimer,  
State of Colorado, United States of America, by Matthias J.G. Ottenberg, this 13 day of  
September, 2000.

WITNESS my hand and official seal pursuant to the authority vested in me as a Notary Public  
by the State of Colorado.



My Commission Expires 07/15/2003

  
Notary Public  
My Commission Expires: 7-15-2003

FROM : 09-15-2000 12:17AM

FAX NO. : SKINNER AND ASSOCIATES

Apr. 10 2001 09:04AM P21  
715 986 6177 P.02

FROM :

FAX NO. :

Sep. 12 2000 08:28AM P9

Date Sept 15 2000


Joseph H. Ferguson  
Douglas H. Ferguson

UNITED STATES OF AMERICA )  
STATE OF MINNESOTA )  
COUNTY OF MEeker }


SUBSCRIBED AND AFFIRMED OR SWORN to before me in the County of meeker, State of Minnesota, United States of America, by Douglas H. Ferguson, this 15 day of September, 2000.

WITNESS my hand and official seal pursuant to the authority vested in me as a Notary Public by the State of Minnesota.

Gonnie M. Bedy  
Notary Public  
My Commission Expires: 1-31-2005



United States Patent & Trademark Office  
Office of Initial Patent Examination -- Scanning Division



Application deficiencies found during scanning:

☐ Page(s) \_\_\_\_\_ of \_\_\_\_\_ were not present  
for scanning. (Document title)

☐ Page(s) \_\_\_\_\_ of \_\_\_\_\_ were not present  
for scanning. (Document title)

☒ *Scanned copy is best available.* Declaration.